

## accessories

### fuel strainers

Stainless steel mesh elements used in the GB, HA and VA fuel filters.  
HASS40 (40 mesh Stainless Steel)  
HASS80 (80 mesh Stainless Steel)



### DF

Fittings for connecting DM 100/150 meters to GE12/24 fuel pumps.



### DG

Fittings for connecting DM 100/150 meters to GP pumps.



### DH

Fittings for connecting DM 100/150 meters to HP pumps.



### DV

Fittings for connecting DM 100/150 meters to PVRH pump.



## fuel nozzles

### CF strainer

This fine mesh strainer may be used in conjunction with Macnaught's C-SERIES range of pumps (C7, C11 and C13) for pumping transmission fluids or hydraulic oils. The CF is included in the pump when the CF7 (CF-51) Oil Pump is ordered.



### HNU nozzle



Suitable for unleaded petrol, this nozzle is designed to fit either the GP RAPIDFLO™ or the HP LITRESTROKE™ pumps.

### MNL manual nozzle – leaded petrol

Flow rate up to 70 L/min  
Inlet: 1" BSP  
Outlet Tube: 1"

### MNU manual nozzle – unleaded

Flow rate up to 45 L/min  
Inlet: 3/4" BSP  
Outlet tube: 13/16"



### ANL automatic nozzle – leaded

Flow rate up to 60 L/min  
Comes complete with 3/4" BSPT (M) x 1" BSPP (F) swivel  
Inlet: 3/4" BSP  
Outlet tube: 15/16"

### ANU automatic nozzle – unleaded

Automatic unleaded nozzle. Flow rate up to 45 L/min  
Inlet: 3/4" BSP  
Outlet tube: 13/16"



### MNHF manual nozzle high-flow – diesel

Dual hi flo diesel nozzle. Flow rate up to 260 L/min  
Inlet: 1 1/2" BSP  
Outlet tube: 1 5/8" "