

WASTE OIL DRAINER 90L

Wide Bowl Extender

Large enough for automatic transmission draining
Bowl diameter 600mm

Filter Mesh Screen In Bowl

Catch foreign items

Telescopic Suction Tube

Easy height adjustment
Extends to 1.85m

Waste Oil Level Tube

Identify oil level inside holding tank

Powder Coated Steel Tank

90L capacity

Oil Bowl

Diameter 400mm

Offset Swivelling Bowl

For easy bowl positioning
Swivelling diameter up to 800mm

5 Suction Probes

For use with vacuum generator

Vacuum Generator with Vacuum Gauge

Easy oil removal through dip stick openings

Handy Tool Tray

Keep tools and accessories within reach

Polyurethane Wheels

Easier manoeuvring over workshop floors



The Lubemate Waste Oil Drainer can be used either as a gravity drainer, or by using the vacuum generator to suck oil out of the dipstick of a vehicle. Once vacuum is pressurised, the drainer is able to work independently without requiring continuous connection to the compressed air system.

L-OD90

TECHNICAL SPECIFICATIONS

- Gravity and air operated waste oil drainer
- Maximum vacuum pressure: 0.85bar
- Draining oil speed: 1.8 - 3LPM
- Maximum oil temperature: 120°C
- Suitable for draining waste oil from engines, gear boxes and differentials of all vehicles
- 1.6m release oil pipe
- Vacuum gauge for checking suction power
- Holds vacuum for up to 24 hours

