

R-SERIES (3:1) AIR OPERATED OIL PUMPS



The 'R' Series range of pumps have been designed and manufactured using a strong metal construction, providing maximum performance and long service life. All the 'R' Series pumps are supplied complete with an in-line air lubricator to help prevent premature wear. Suitable for oils up to SAE140 viscosity and premix coolants. The ideal choice for remote mount or integration into lubrication systems.

Long service life

Supplied with In-line lubricator to prevent excess wear and extend service life

Air inlet (1/4"NPT)

Robust and Durable Design

Heavy duty aluminium and steel air motor construction

Sliding bung adaptor (2"BSP)

For all R-Series pump models



Heavy duty construction
For long reliable service life

Maximize Performance life
Large exhaust ports integrated to prevent icing

Oil outlet (3/4"BSPT or NPT)
For all R-Series pump models

Oil inlet (1"BSPT or NPT)
On all stub pump models

P/N: R300S-01

TECHNICAL SPECIFICATION

Free Flow Rate: 23l/m

3:1 Ratio pump for medium flow / larger distances

Supplied with airline lubricator and 2" bung adaptor

Suitable for oils to SAE140 viscosity, coolants, kerosene, diesel

PACKAGE INCLUDES

Pump Unit

Owner's Manual

APPLICATIONS

Installations where there are long distance and high flow requirements